


# Product specification Eurologik casement windows



## EUROLOGIK STANDARD CASEMENT TRIPLE GLAZED OUTWARD OPENING, INTERNALLY GLAZED

### Profiles

- Eurocell **eurologik** 70mm system
- Standard outer frame

### Reinforcements

- PVC-U Thermal Inserts

### Cill options

**Standard:** 85mm (130mm\*), 150mm (195mm\*) and 180mm (225mm\*)

\* When used with cill extender

### Accreditations

- Eurocell **eurologik** profile system is BBA certified
- **BS EN 12608, BS 7412, BS 6375, BS 7950**

### Style



Ovolo



Chamfered


### Thermal performance

System	Config	Glass 1 (external)	Glass 2 (triple)	Glass 3 (internal)	Gas fill	Spacer bar	Reinforcing	U Value
<b>eurologik</b>	4/12/4/12/4	Float	SG Planitherm One	SG Planitherm One	Krypton	Swisspacer V	PVC-U TI	0.8
<b>eurologik</b>	4/12/4/12/4	Float	SG Planitherm One	SG Planitherm One	Argon	Swisspacer V	PVC-U TI	0.9
<b>eurologik</b>	4/12/4/12/4	Float	SG Planitherm Plus	SG Planitherm Plus	Argon	Superspacer	PVC-U TI	1
<b>eurologik</b>	4/12/4/12/4	Float	Pilkington K S	Pilkington K S	Argon	Swisspacer V	PVC-U TI	1

**Note:** The above calculations should be used for guideline purposes only. Other options also available. To have **eurologik70** with standard outerframe triple glazing performance simulated, please contact Eurocell's technical department.

### Colour options

#### Standard colours



#### Non-standard options

Eurocell profiles are available in any colour from our made-to-order range. These are available on a three-week lead-time.

\* White Ash and Irish Oak available in Ovolo styles only. Anthracite Grey and Slate Grey available in Chamfered only

### Min / max sizes

If the windows are to be manufactured are outside these sizes, please consult Eurocell's technical department.

System	Width (mm)	Height (mm)
Casement windows (top hung) Espag	Max: 1200 Min: 320	Max: 1350 Min: 375
Casement windows (side hung)	Max: 750 Min: 400	Max: 1500 Min: 320
All fixed sizes (fixed)	Max: 3000	Max: 2400 (combined width & height 5400)